

ZB Series

Technical Data

Model	ZB50KQ ZB50KQE	ZB58KQ ZB58KQE	ZB66KQ ZB66KQE	ZB76KQ ZB76KQE	ZB88KQ	ZB92KC ZB92KCE	ZB11MC ZB11MCE
Motor Type	TFD	TFD	TFD	TFD	TFD	TWD	TWD
Nominal power(HP)	7.5	8	9	10	12	13	15
Discharge Capacity(m ³ /hr)	19.8	22.1	25.7	28.8	33.2	35.6	42.1
Startup Current(LRA)(AMP)	90~100	86~95	100~111	110~118	110~118	151~167	179~198
Rated Load Current(RLA)(AMP)	14.3	16.4	17.3	19.2	22.1	21.5	24.3
Max Continuous Current(MCC)(AMP)	20.0	23.0	24.2	26.9	31.0	30.1	34.0
Crankcase Heater(W)	90	90	90	90	90	70	70
Connection Tube size(inch)							
Discharge Tube outer Diameter	7/8	7/8	7/8	7/8	7/8	1 1/4	1 3/4
Suction Tube outer Diameter	1 1/8	1 1/8	1 3/8	1 3/8	1 3/8	1 3/4	2 1/4
Dimension(mm)							
Length	263.6	263.6	263.6	263.6	263.6	320.8	320.8
Width	284.2	284.2	284.2	284.2	284.2	357.1	349.2
Height	479.5	477	546.1	546.1	546.1	532.4	591.8
Mounting pants installation size (hole size)	190X190 (8.5)	190X190 (8.5)	190X190 (8.5)	190X190 (8.5)	190X190 (8.5)	220X220 (8.5)	220X220 (8.5)
Oil Recharge(L)	2.51	2.51	3.25	3.25	3.25	4.14	4.14
Weight(kg)							
Net	58.97	59.87	60.33	65.32	65.32	103	112
Gross						110	119