



CATALOG COIL VAN DANFOSS BF230CS (018F6282)

Nguồn cấp 220-230VAC, 50/60Hz; IP67, cáp sẵn dài 1 mét

Contact: 0982 67 24 67 - online@congnhieplanh.com

Details

Gross weight	0.35 kg
Net weight	0.31 kg
EAN	5702428025003
Actuator size	13.5 mm
Ambient temperature range [°C] [Max]	50 °C
Ambient temperature range [°C] [Min]	-40 °C
Ambient temperature range [°F] [Max]	120 °F
Ambient temperature range [°F] [Min]	-40 °F
Approval	LLC CDC TYSK
Cable diameter [mm]	6.6 mm
Cable length [in]	40 in
Cable length [m]	1 m

Coil connection	CABLE
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Conductor area [mm2]	3 x 0.75 mm2
Duty rating	Continuous
Electrical connection	Cable
Electrical connector	3 core cable
Enclosure rating IP	IP67
Frequency [Hz]	50/60 Hz
Further information	Moulded cable
Identical product	018F8232
Packing format	Multi pack
Parts Program name	EV210B EV212B EV220B 15 - 50 EV220B 6 - 22 EV220B 65 - 100 EV222B EV224B EV227B EV250B EV251B
Power consumption 50Hz [VA]	31 VA
Power consumption 60Hz [VA]	24 VA
Power consumption [W] 50Hz	16 W
Power consumption [W] 60Hz	14 W

Product accessories	Solenoid coil accessories
Product group	Solenoid valves
Product name	Solenoid coil
Quantity per packing format	24 pc
Rel. Humidity [% RH] [Max]	100 %
Rel. Humidity [% RH] [Min]	0 %
Serviceable	No
Spare part number	018F6282
Supply voltage 50Hz Max [V]	230 V
Supply voltage 50Hz Min [V]	220 V
Supply voltage 60Hz Max [V]	230 V
Supply voltage 60Hz Min [V]	220 V
Supply voltage [V] AC [Max]	230 V
Supply voltage [V] AC [Min]	220 V
Type	BF230CS
Type designation	BF230CS